



# BOOM FLAIL MOWER

[TRACKLESSVEHICLES.COM](http://TRACKLESSVEHICLES.COM)

Almost every municipality has several areas which are challenging, unsafe or impossible to mow. Ditches, steep inclines, over guard rails and waters-edge cutting become problems of the past once the Boom Flail Mower enters the scene.

The attachment is front-mounted for better visibility compared to side or rear mount boom flails, resulting in less operator fatigue and safer operation. The compact size of the MT and Boom Flail decreases interference with passing traffic compared to larger agricultural-type tractor/mower combinations.

Finally, hydrostatic speed control allows the operator to react to oncoming obstacles for optimum safety and productivity.

**CONTACT TRACKLESS TODAY**

**CALL** 519-688-0370

**EMAIL** [info@tracklessvehicles.com](mailto:info@tracklessvehicles.com)

**VISIT** 55 Thunderbird Drive, PO Box 244,  
Courtland ON, Canada N0J 1E0



## GENERAL SPECS

### WIDTH OF CUT

43.5"; overall width of head  
53.5"

### HORIZONTAL REACH

13.5' from center of MT to  
outside cut

### VERTICAL REACH

13.5'

### CUTTING BLADES

32

### LEVEL GROUND CUTTING COVERAGE

11', starting 5" inside outer tire

### BELOW GRADE CUT

53"