

# BOOM FLAIL MOWER SPECS



| FEATURES                                                                      | STANDARD | OPTIONAL |
|-------------------------------------------------------------------------------|----------|----------|
| Width of cut 43.5" (1105 mm); overall width of head 53.5" (1359 mm)           | ✓        |          |
| Horizontal reach 13.5' from center of MT to outside cut                       | ✓        |          |
| Below grade cut 53" (1346 mm)                                                 | ✓        |          |
| Vertical reach 13.5' (4115 mm)                                                | ✓        |          |
| Overall level ground cutting coverage: 11', starting 5" inside the outer tire | ✓        |          |
| 6" diameter gauge                                                             | ✓        |          |
| 32 cutting blades                                                             | ✓        |          |
| Bolt on safety screen for side window included                                | ✓        |          |
| Trackless yellow finish                                                       | ✓        |          |
| Boom flail extension                                                          |          | ✓        |

\*Dual tires are required for this attachment.

| MODEL            | LENGTH*       | WIDTH*        | HEIGHT*       | WEIGHT*            |
|------------------|---------------|---------------|---------------|--------------------|
| Boom Flail Mower | 66" (1676 mm) | 84" (2134 mm) | 85" (2159 mm) | 2329 lbs (1056 kg) |

**FOR MORE INFORMATION PLEASE VISIT [TRACKLESSVEHICLES.COM](http://TRACKLESSVEHICLES.COM)**

\*All measurements provided are approximate and based on shipping dimensions.