

COLD PLANER SPECS



| FEATURES | STANDARD | OPTIONAL |
|---|----------|----------|
| Planing width 16" (406 mm) | ✓ | |
| Planing depth 0 to 6" (0 to 152 mm) | ✓ | |
| 50 picks on asphalt drum, 160 picks on concrete drum | ✓ | |
| Hydraulic controlled manoeuvrability: <ul style="list-style-type: none"> - Tilt: ± 19° - Depth: 0 to 6" (0 to 152 mm) - Side Shift: 0 to 22" (0 to 559 mm) | ✓ | |
| Double reduction planetary drive | ✓ | |
| Drum torque 25,000 in/lbs @2000 psi | ✓ | |
| Drum wall thickness 5/8" (15.88 mm) | ✓ | |
| Trackless yellow finish | ✓ | |
| Spray nozzle kit for cold planer | | ✓ |

| MODEL | LENGTH* | WIDTH* | HEIGHT* | WEIGHT* |
|-------------|---------------|---------------|---------------|-------------------|
| Cold Planer | 69" (1752 mm) | 70" (1778 mm) | 45" (1143 mm) | 1880 lbs (852 kg) |

FOR MORE INFORMATION PLEASE VISIT TRACKLESSVEHICLES.COM

*All measurements provided are approximate and based on shipping dimensions.