

DOUBLE TRIP SNOWPLOW SPECS



| FEATURES | STANDARD | OPTIONAL |
|--|----------|----------|
| Overall length: 60" (1524 mm) | ✓ | |
| Blade height: 32" (813 mm) | ✓ | |
| Cutting edge 1/2" x 6" hardened steel, reversible and replaceable | ✓ | |
| Power angling to 30° in either direction by 2 single acting cylinders | ✓ | |
| Cushion valve to help protect plow if an object is stuck | ✓ | |
| 2 trip mechanisms, plow trip is 35° and the cutting edge trip is 40° | ✓ | |
| 2 extension trip springs for the mouldboard, springs are 2" in diameter | ✓ | |
| 2 compression trip springs for the cutting edge trip springs shall be 5" in diameter x 5/8" wire | ✓ | |
| Supported by a retractable leg which allows the tractor to drive into the plow attaching frame | ✓ | |
| Trackless yellow finish | ✓ | |

| MODEL | LENGTH* | WIDTH* | HEIGHT* | WEIGHT* |
|----------------------|---------------|---------------|--------------|------------------|
| Double Trip Snowplow | 49" (1244 mm) | 60" (1524 mm) | 32" (812 mm) | 700 lbs (317 kg) |

FOR MORE INFORMATION PLEASE VISIT TRACKLESSVEHICLES.COM

*All measurements provided are approximate and based on shipping dimensions.