

# FRONT FLAIL MOWER



[TRACKLESSVEHICLES.COM](http://TRACKLESSVEHICLES.COM)

## MOW LIKE NO OTHER.

The Front Flail Mower was designed to cut heavier grass, weeds, scrub and light brush where a standard rotary lawn mower could not cope. An enclosed mower housing and rubber safety skirts keep the cut grass, mulch and other debris within the cutting chamber. This allows for safe mowing near roads, parks and other busy areas.

Large gauge wheels and a full-width gauge roller give the mower front-to-rear flexibility, allowing it to follow ground contours, producing an even cut without turf damage.

### CONTACT TRACKLESS TODAY

**CALL** 519-688-0370  
**EMAIL** [info@tracklessvehicles.com](mailto:info@tracklessvehicles.com)  
**VISIT** 55 Thunderbird Drive, PO Box 244,  
Courtland ON, Canada N0J 1E0

## GENERAL SPECS

### WIDTH OF CUT

74" (1879 mm)

### CUTTING HEIGHT

1" to 4" (25 mm to 102 mm)

### GAUGE WHEELS

Two 16" x 4" laminated

### GAUGE ROLLER

6" diameter steel, full width

### ROTOR TUBE

4" diameter with one 7/16" shaft

### BLADES

33, 2.75" wide blades (can be resharpened)

